

Technical Information on Automatic Pipeline Washers

Model	Water inlet Size	Water Outlet Size	Flow Rate
Model 12 Model 21	½" I.D.	½" I.D.	5.29 gallons per minute @ 40 PSI
Model 32 Hi-Flow Model 31 Hi-Flow	¾" I.D.	5/8" I.D.	7.37 gallons per minute @ 40 PSI
Model 23 with ¾" external valve		¾" valve	8.84 gallons per minute
Model 23 with 1" external valve		1" valve	11.79 gallons per minute
Model 23 with 1-1/2" external valve		1-1/2" valve	17.68 gallons per minute
Model 24 or 25	Only for Chemical Dispense Rate	Only for Chemical Dispense Rate	8 ounces per minute

June 24th 1996



**Holdren
Brothers, Inc.**

METAL FABRICATORS

12/89

301 Runkle • West Liberty, Ohio 43357
(513) 465-7050

UNITS	PRESSURE			
	20 PSI	30 PSI	40 PSI	50 PSI
MODELS 1,2,3,12,21	3 GPM	4 GPM	5 GPM	6 GPM
MODELS 31,32	5 GPM	6 GPM	7.5 GPM	8 GPM
MODEL 11	19.5 GPM	24.5 GPM	28 GPM	33 GPM
MODEL 33 w/ 3/4 external valve	25.5 GPM	32.5 GPM	38 GPM	44.5 GPM
MODEL 33 w/ 1-1/2 external valve	88 GPM	110.5 GPM	124 GPM	135 GPM

** THESE ARE APPROXIMATE RATES OF FLOW **